




LSM Series High-Power LEDs



UV-Shortwave NIR LEDs for Fluorescence Excitation and More

LSM LEDs are ideal for fluorescence excitation and other spectroscopy measurements. The LEDs are available in discrete wavelengths ranging from 265-880 nm and in a warm white option with color temperature of 3000K.

LSM LEDs provide highly efficient coupling of LED light into an optical fiber, ensuring high signal output for applications across UV, Visible and Shortwave NIR wavelengths. The single-channel LDC-1 driver and controller unit enables simple LED programming and waveform display, and allows users to monitor characteristics such as LED power output and temperature.



At a Glance

Driver and Controller

Power consumption: 2A (maximum) at 15 VDC

Power requirements: 15 VDC power supply, 30W maximum

Display: 3.5" 480 x 320 resolution color graphics display w/resistive touch screen

Signal sources: Internal DC

Internal Sine, Triangle and Square waves

External Modulation Input: 0-5V signal or driven with function generator

Safety & regulatory: CE

LEDs

UV wavelengths: 265 nm, 280 nm, 310 nm, 365 nm

Visible wavelengths: 405 nm, 470 nm, 533 nm, 635 nm, 880 nm

Broadband: Warm White (3000K)

Environmental conditions: Temperature: 0° C to 50° C

Humidity: <85% (relative humidity, non-condensing)

Altitude: 0-3050 m (0-10,006 ft.)

Safety & regulatory: CE

Additional Advantages of LSM LEDs

With the LDC-1 single-channel driver and controller, users can select the appropriate power level to maintain LED thermal stability and maximize bulb life, or select a pulse mode with varying on/off times when an experiment requires this. Individual wavelengths can be changed by simply hot swapping the modules connected to the LDC controller.

In addition, the Internal Modulation Modes allow users to experiment with different waveforms and frequencies. These modulation techniques are useful for applications including the testing of commercial phosphors, which require time-resolved quality analysis of phosphorescent properties.

